



FINSA

soluciones en madera

FIBRANATUR E-Z TEX

TECHNICAL DATA - AVERAGE VALUES

Rev: 07/04/2020

| PROPERTIES | TEST METHOD | UNITS | TEXTURE | | | |
|-----------------------------------|-------------|-------|---------|------|--------|--------|
| TEXTURE | | | VETA | FUJI | MOJAVE | PRISMA |
| ORIENTATION IN BOARD | | | | | | |
| | | | | | | |
| DIMENSIONAL MOVEMENT LENGTH/WIDTH | EN 318 | % | 0,4 | 0,4 | 0,4 | 0,4 |
| DIMENSIONAL MOVEMENT THICKNESS | EN 318 | % | 6 | 6 | 6 | 6 |

TOLERANCE ON NOMINAL DIMENSIONS

| PROPERTIES | TEST METHOD | UNITS | TEXTURE | | | |
|----------------------|-------------|-------|---------------------------|------------|------------|------------|
| | | | BETA | FUJI | MOJAVE | PRISMA |
| THICKNESS | EN 324-1 | mm | Nominal thickness +/- 0,5 | | | |
| LENGTH AND WIDTH | EN-324-1 | mm | +/-2 mm/m, max 5mm | | | |
| SQUARENESS | EN 324-2 | mm/m | +/-2 | | | |
| EDGE STRAIGHTNESS | EN-324-2 | mm/m | +/-1,5 | | | |
| ALIGNMENT OF TEXTURE | | mm/m | 1 | | | |
| MAX DEEP TEXTURE | | mm | 0,6 +/-0,2 | 0,5 +/-0,2 | 0,5 +/-0,2 | 0,7 +/-0,2 |

| | |
|--------------------|--|
| FORMALDEHYDE: | Very low emission board $\leq 0,05$ ppm EN 717-1. Fulfills with EPA TSCA TITLE VI and CARB P2. |
| REACTION TO FIRE: | D-s2,d0 |
| ASPECT: | <p>Textured in one side, always with MDF as raw board</p> <p>Color differences in the textured face could be seen</p> <p>Color of the textured board may differ from the raw one and between different textures</p> <p>No flatness specification is given</p> <p>Coordinated texture: in Mojave and Prisma textures (the pattern starts on all the boards at the same point)</p> |
| HANDLING/ STORAGE: | <p>It must always be stored under cover and on a flat surface,</p> <p>65% of ambiental moisture is the ideal condition for storage, dryer or wetter environments should be avoided.</p> <p>It must never be in direct contact with water</p> <p>Resting blocks must always be lined up with the vertical.</p> <p>Never pile up more than 4 heights.</p> <p>If the packaging is damaged during its handling, it must be packed again so the product is correctly preserved.</p> |
| USAGE TIPS: | Interior use in dry conditions. |
| LACQUERING: | <p>Lacquering recommendations from ILVA:</p> <p>https://drive.google.com/open?id=1AVQ0th70Zke3d_p4hK7-0yNladf2BEaM</p> |
| FINISHING: | <p>Recommendations for handling and finishing</p> <p>https://drive.google.com/open?id=1_JmYAGyJaisFJ1ZBgoalDi3ZxuEeh46K</p> |